

## Digital Ultrasonic Cleaner with 1 Frequency

**AELAB** Digital ultrasonic cleaners are suitable to clean irregular and complex specialized instruments, components and PCBs of sundry shops, workshops, factories etc; smash, emulsify, scatter, hydrolyze, extract, degas certain analyzed stuffs in labs.

### Features:

- ◆ Die casting stainless steel tank.
- ◆ Industrial grade integrated circuit.
- ◆ 0~80 C temperature range.
- ◆ 1~99 minutes working time.
- ◆ Degassing and degreasing function.
- ◆ 28KHz for gross rinse or 40KHz for intensive rinse.
- ◆ Auto stand-by, sleep, and wake-up by one key-press mode.
- ◆ Digital controller of high-precision and a long service-life.



### Technical Specifications:

Model No.	Tank Size (mm)	Overall Size (mm)	Capacity (L)	Frequency (KHz)	Ultrasonic Power (W)	Heating Power (W)	Timing (min)	Temp. (C)	Drainage
AE-130D	150*140*65	190*170*195	1.3	28 or 40	60	100	1~99	0~80°C	None
AE-200D	150*140*100	190*170*230	2	28 or 40	60	100	1~99	0~80°C	None
AE-300D	240*140*100	270*170*240	3.2	28 or 40	120	100	1~99	0~80°C	None
AE-400D	300*155*100	312*162*240	4.5	28 or 40	120	100	1~99	0~80°C	None
AE-600D	300*155*150	330*180*330	6.5	28 or 40	180	300	1~99	0~80°C	Yes
AE-1000D	300*240*150	330*270*330	10	28 or 40	240	300	1~99	0~80°C	Yes
AE-1500D	330*300*150	360*330*330	15	28 or 40	360	400	1~99	0~80°C	Yes
AE-2200D	500*300*150	500*330*330	22	28 or 40	480	500	1~99	0~80°C	Yes
AE-3000D	500*300*200	550*330*380	30	28 or 40	600	500	1~99	0~80°C	Yes