

SK9600 Hematology Analyzer

Feature:

- 3-part differentiation of WBC, 24 parameters, up to 60 samples test per hour
- Electrical resistance for counting and SFT method of Hemoglobin
- Low sample consumption : venous 9.8 ul, prediluted 20 ul for twice testing one time
- 8.4" inches color touch screen, Windows interface all testing parameter displayed simultaneously
- Windows operation system graphical buttons mouse and keyboard operation
- Automatic diluting , Mixing , rinsing and clog clearing
- Automatically sample probe cleaning (inside and outside)
- Large storage capacity: up to 10,000 samples +3 histograms
- Internal thermal-sensitive printer or external printer.
- RS232 interface, PC connecting

Main Technical Specifications:

- Methodology: Electrical resistance for counting, hemiglobincyanide method and SFT method for hemoglobin
- Parameter: 3-part differentiation of WBC; 21 parameters and 3 color histograms (WBC, RBC, PLT)
- Work mode : double Channel + unique Hemoglobin test system
- Sample volume: 9.8 μ L for Venous and capillary mode, 20 μ L for prediluted mode
- Throughput: More than 60 samples per hour, operatable 24 hours a day, auto sleeping and waking-up functions
- Storage: up to 100000 sample results including histograms can be stored, convenient for inquiry and management of history data
- Operation language: English
- QC control : X-B, L-J, X , SD, CV %
- Reference Value Setting : Male , Female, Children, Neonate
- Input / output : RS232, parallel printer and keyboard
- Print : Graphic thermal printer with various printing format, optional external printer
- Temperature : 18 $^{\circ}$ C - 30 $^{\circ}$ C, wet \leq 10-90%
- Power supply : 220 V \pm 22 VAC, 50 \pm 1Hz
- Dimension : 33 CM (L) * 38 CM (W) * 43 CM (H)
- Weight : 20 KG

Precision:

Parameters	linear range	CV %
WBC (10 ⁹ / L)	0.0 - 99.9	\leq 2%
RBC (10 ¹² / L)	0.0 - 9.99	\leq 1.5%
MCV (fL)	40-150	\leq 0.5%
PLT (10 ⁹ / L)	0-999	\leq 4.0%
HGB (g/L)	0.0-300.0	\leq 1.5%

Parameters:

WBC, Lymph#, Mid#, Gran#, Lymph%, Mid%, Gran%, RBC, HGB, HCT, MCV, MCH, MCHC, RDW-CV, RDW-SD, PLT, MPV, PDW, PCT, P-LCR, P-LCC
 3 - histograms : WBC, RBC and PLT





SK9600

Hematology Analyzer

- ④ 3-part differentiation of WBC, 24 parameters, double channel counter
- ④ Volume measurement by time ,less mistake
- ④ 8.4 inches color touch screen
- ④ RS232 interface, PC connecting
- ④ Waste full alarm automatically

