

## LAC-N Climate Chamber

### Features:

- ◆ Two sets of refrigeration systems automatically switch in turn to ensure that long time operation without failure.
- ◆ International brand fluorine-free compressor, environment friendly and reliable.
- ◆ International brand humidity sensor, high accuracy for humidity.
- ◆ Double door design. The inner door is made of tempered glass for easy observation, the outer door with magnetic strip, good sealing.
- ◆ Large LCD screen to display temperature and humidity, light intensity. Multi-segment timing program control technology, high precision.
- ◆ Polished stainless-steel chamber, moveable grids can be freely adjusted, easy for cleaning. Powder coating steel housing.
- ◆ External water tank. Electric heater humidification system.
- ◆ It can simulate the temperature changes of nature during the day and night.
- ◆ JAKEL circulation fan, unique air duct structure, effectively guarantee the temperature stability inside the box.
- ◆ The parameters can be saved automatically in case of power failure, and the original setting programme will be run when power is restored.
- ◆ In case of failure of the incubator, a fault message appears on the LCD display, and the operational faults can be seen at a glance.
- ◆ Equipped with leakage protection and a spare mechanical thermostat to ensure the product work normally even the main temperature control failed (for heating).
- ◆ USB port for recording data.



### Safety Device

Over temperature protection

Compressor over current protection

Over compressing protection

Water shortage protection

Heater overheats protection

Audible and visual alarm system

### Options:

CO<sub>2</sub> control system

Note: LAC series are with humidity control, LB series without humidity control.

### Specifications:

Note: LAC series are with humidity control, LB series without humidity control.

Model	LAC-175-N	LAC-275-N	LAC-375-N	LAC-475-N	LAC-800-N	LAC-800-D-N	LAC-107-5-N	LAC-107-5D-N	LAC-16-75D-N
Chamber Volume	175L	275L	375L	475L	800L	800L	1075L	1075L	1675L
Temp. Range	With light:10~55℃				Without light:0~55℃				
Temp. Stability	≅±1℃								



Display Resolution	0.1°C									
Temp. Uniformity	≅ ±1°C									
Humidity Range	30~95%RH									
Humidity Deviation	±3%RH									
Light Intensity (LX)	0~12000 6 levels control	0-20000 6 levels control	0-25000 6 levels control	0-30000 6 levels control	0-30000 6 levels control	0-30000 6 levels control	0-30000 6 levels control	0-30000 6 levels control	0-30000 6 levels control	0-30000 6 levels control
Power Rating	1650W	2200W	2700W	2900W	4200W	4200W	4200W	4200W	4200W	4600W
Power Supply	AC220V, 50HZ									
Operating Temperature	+5~35°C									
Chamber Size(W×D×H)cm	45*42*9 3	58*51*9 4	59*55*11 6	70*55*12 5	96*61*1 37	126*50* 127.5	95*70*1 60	126*67* 127.5	146*85 *135	
Exterior Size(W×D×H)cm	65*73*1 75	77*74*1 71	78*87*19 1.5	88*87*19 9.5	110*93* 227	141.8*7 8.1*195	101*90* 234	141.8*9 5.1*195	162.5* 122*20 4	
Number of Grids(Std/Max)	3/16	3/16	3/21	3/22	3/22	6/18 (2 grids in one level)	3/22	6/18 (2 grids in one level)	6/20 (2 grids in one level)	