

Horizontal Drying Oven

◎High precision and large density sample drying treatment.

Characteristics:

- Horizontal air type, high space utilization and good temperature uniformity.
- 101: Forced fan cooling intake structure, the maximum working temperature <50 °C, the fan long-term longevity operation.
- 202:Classical natural convection drying method.
- New anti-hot handle.



Patent No. : ZL 2018 3 0094606.5

Main technical parameters:

Model		101-0A/101-0AB	101-1A/101-1AB	101-2A/101-2AB	101-3A/101-3AB
		202-0A/202-0AB	202-1A/202-1AB	202-2A/202-2AB	202-3A/202-3AB
Cycle Mode		101 means Forced convection; 202 means Natural convection			
Function	Temp. Range	RT+10~250℃			
	Temp. Resolution Ratio	0.1℃			
	Temp. Motion	± 1℃			
	Temp. Uniformity	101 model ± 2.5%, 202 model ± 3.5%			
Structure	Inner Chamber	B model:High quality stainless steel; without B model:High strength galvanized sheet			
	Outer Shell	Cold rolling steel electrostatic spraying exterior			
	Insulation Layer	High quality rock wool board(with CE)			
	Heater	101 model with Stainless steel electric heating tube; 202 model with Nickel chromium alloy heating wire			
	Power Rating	1.2kW	1.6kW	2.3kW	3.0kW
Exhaust Hole		φ 35mm top(with function of test hole)			
Controller	Temp. Control Mode	Two temperature section PID intelligent			
	Temp. Setting Mode	Touch button setting			
	Temp. Display Mode	LED Digital display			
	Timer	0-9999min(with timing wait function)			
	Operation Function	Fixed temperature operation, fixed timing operation, auto stop.			
	Additional Function	Sensor deviation correction, temperature overshoot self-tuning, internal parameter locking, power-off parameter memory			
	Sensor	PT100			
Safety Device		Over temperature sound-light alarm			
Specification	Inner Chamber Size(W*L*H)(mm)	350*350*350	450*350*450	550*450*550	600*500*750
	Exterior Size (W*L*H)(mm)	652*472*587	752*472*687	852*572*786	902*622*986
	Packing Size (W*L*H)(mm)	745*605*745	845*605*850	945*705*950	955*755*1150
	Volume	43L	71L	136L	225L
	Max Shelf Number	9	13	17	25
	Load Per Rack	15kg			
	Shelf Space	25mm			
	(50/60HZ)Current Rating	AC220V/5.5A	AC220V/7.3A	AC220V/9.1A	AC220V/13.6A
	NW/GW (kg)	40/46	45/50	62/68	77/96
Accessory	Shelf	2			
	Shelf Frame	4			
Optional Accessories		Shelves			